

# Neural Networks Loss Landscape Convergence in Different Low-Dimensional Spaces

Tem Nikitin Nikita Kiselev

Moscow Institute of Physics and Technology

April 1, 2025

# Problem Statement

- Neural networks achieve higher accuracy with larger datasets.
- However, computational resources limit training possibilities.
- Key question: **When does additional data stop reshaping the loss landscape?**

# Proposed Method

- Analyze loss landscape via Hessian eigenvectors.
- Project high-dimensional parameter space onto lower-dimensional space.
- Utilize Monte-Carlo methods to approximate landscape changes.

# Main Idea

- **Hessian-based projections** identify primary curvature directions.
- Calculate a  $\Delta$ -function to quantify changes when increasing dataset size:

$$\Delta_k = \int (L_k(w) - L_{k-1}(w))^2 p(w) dw$$

- Identify the threshold at which further data does not significantly alter landscape.



# Neural Networks Loss Landscape Convergence in Different Low-Dimensional Spaces

**Goal:** Measure how the loss function changes as the training set size grows:

$$\Delta_k = \mathbb{E}_{p(\mathbf{w})} \left( \mathcal{L}_k(\mathbf{w}) - \mathcal{L}_{k-1}(\mathbf{w}) \right)^2.$$

**Method:**

- **Monte Carlo:** Generate points near the minimum according to  $p(\mathbf{w})$  and average the differences.
- **Hessian Eigenvectors:** Use directions with the largest eigenvalues to focus on key curvature components.



# Experiment Results

- Experiments conducted on MNIST and Fashion-MNIST datasets.
- Low-dimensional visualization clearly illustrates stabilization.
- Verified theoretical bounds empirically.

# Practical Implications

- Enables identification of minimal viable dataset size.
- Reduces computational cost significantly.
- Provides guidelines for efficient data collection.

# References

-  Soydナー, D. *Optimization algorithms for deep learning*, 2020.
-  Wu et al. *Loss landscape and generalization*, 2017.
-  Petersen, Pedersen. *The matrix cookbook*, 2012.
-  Deng, L. *MNIST database*, 2012.
-  Xiao et al. *Fashion-MNIST*, 2017.
-  Kiselev, Grabovoy. *Unraveling the Hessian*, 2024.
-  Sagun et al. *Hessian analysis of networks*, 2018.